

# ULTIMATE SERIES

## *Ceiling White GOLD* *Super Premium Acrylic for interiors*



Astec Paints Australasia Pty. Ltd.

ACN: 120 962 245 ABN: 76 120 962 245

*A Specialty for Ceilings with excellent hiding power and an extra flat finish to cover surface imperfections. Designed with Non-Splatter Acrylic Technology, Unique to Astec.*

*A super premium Acrylic Ceiling White for interiors that has excellent hiding power and an extra flat finish to cover surface imperfections. With Astec's Unique Non-Splatter Acrylic Technologies, the product provides a long lasting finish that bonds extremely well to the surface. The product is fortified with unique flow and levelling agents to provide excellent ease in application, resulting in a smooth, and uniform cover.*

### Ultimate Series Ceiling White GOLD

#### **PRINCIPAL USE**

Interior, paper faced boards, plaster, fibrous plaster, cement sheet, masonry and brick. Do not use this product for any other purpose than as specified by our literature.

#### **SURFACE PREPARATION**

**Previously Painted Surfaces** All surfaces must be clean dry and free of contaminants. Remove dirt or dust and any grease with a household detergent or sugar soap. Scrape of any loose or flaking paint on existing painted surfaces then sand any remaining paint to a flat finish to provide a sound surface. Any existing paint that exhibits a complete lack of adhesion should be entirely removed for the best results. Fill any cracks or holes with a suitable filler, sand smooth and dust off prior to coating application. Coat any ferrous type nails first with Astec Rustraint or Oil Based Undercoat to avoid rust spotting. Apply one coat of Astec Acrylic Primer Undercoat to any repairs or any areas which have an uneven gloss.

**New Unpainted Paper Faced Wallboards** Lightly sand any joints where necessary, brush down the surface to remove any dust, apply one coat Astec Acrylic Primer Undercoat to the entire surface. Apply two coats Ultimate Series Ceiling White.

**New Unpainted Plaster and Fibrous Plaster** Brush down to remove any surface dust, for best results apply one coat Astec Oil Based Undercoat or Astec Rivett. If Rivett is used follow with one coat Astec Acrylic Primer Undercoat. Apply two coats Ultimate Series Ceiling White.

**New Unpainted Fibro Cement Sheet,** Brush down to remove any surface dust, for best results apply one coat Astec Rivett or Rapid Seal. For best results apply one coat Astec Acrylic Primer Undercoat to the entire surface. Apply two coats Ultimate Series Ceiling White.

**New Unpainted Masonry and Brick** Brush down to remove any surface dust, where it is not possible to completely remove loose surface particles from masonry, apply Astec Rivett, which will bind the surface to a hard finish prior to painting. Apply one coat Astec Acrylic Primer Undercoat to the entire surface. Apply two coats Ultimate Series Ceiling White.

**New Timber** Treat all nails with Astec Rustraint allow to dry then fill all nail holes with a suitable wood filler. For optimum adhesion sand all dressed timber. On tannin rich timbers, (Oregon, Cedar ext), prime with Astec Oil Based Undercoat to prevent staining of light tinted colours. For maximum performance on all other timbers apply Astec Acrylic Primer Undercoat, sand smooth dust off. Apply two coats Ultimate Series Ceiling White.

**Mould Infested Areas** Wash down using a stiff brush with Sodium Hypochlorite, (Chlorine), or a household bleach and water to remove the mould then apply one coat Astec Barrier, an under film mould retardant.

**Window Painting** Use sparingly on all contact areas, open and close windows within 30 minutes and there after at 4 hour intervals over the following 24 hours.

**P.V.C.** Sand the entire surface and wipe down with Astec all Purpose thinners prior to any coating application.

**NOTE** Do not apply to surfaces that have had wax or silicone based materials previously applied.

#### **SAFETY DIRECTIONS**

Keep out of reach of children, provide adequate ventilation during use, do not dispose of left over paint down any drainage systems.

**FIRST AID**

Eye contact: Flush immediately with large amounts of water for at least 15 minutes, holding eyelids open. Call a physician if irritation persists.

Swallowed: Call a physician immediately if swallowed. Give patient water to drink. Contact Astec Paints for the relevant Material Safety Data Sheet.

**Manufactured by Astec Paints Australasia Pty Ltd**

22-24 Pinn Street, St. Marys, South Australia, 5042. A.C.N. No. 120 962 245 Ph +618 8297 2000

**PRODUCT DATA**

**Gloss level:** 8%

**Wash up:** Water

**Performance:** Interior/Exterior

**Application:** Brush Spray or Roller.

**Coverage:** 14 to 16 m<sup>2</sup> per litre (substrate dependant)

**Thinning:**

Add up to 5% fresh clean water for spray or hot weather applications

**Mixing:**

Use a broad flat paddle or paint wacker in a scooping action to thoroughly pull from the can's base


**Drying time at 25° C**

**Touch dry:** 1/2 hour

**Re-coat:** 2 hours

**LIMITATIONS**

Ultimate Series Ceiling White GOLD is a water based material, therefore, should not be applied during inclement weather or when precipitation or freezing are imminent.



The technical data furnished herein is based upon data believed by Astec Paints to be true and accurate at the time of writing, however, no guarantee of accuracy is given or implied and is subject to change without notice.

This information is given in good faith for the assistance of users. No legal warranty expressed or implied is made as to its accuracy, completeness or otherwise.

Every person dealing with this material herein does so at their own risk absolutely and must make independent determinations of suitability and completeness from all sources to ensure their proper use.

We have no control over the condition under which these products are stored, handled or used, therefore our recommendations must not be regarded as a mounting to legal warranty or as involving any liability on us.



Astec Paints Australasia Pty. Ltd.  
22-24 Pinn Street, St. Marys,  
South Australia 5042  
PO Box 321, Melrose Park, S.A. 5039

Web: [www.astecpaints.com.au](http://www.astecpaints.com.au)  
Email: [enquiries@astecpaints.com.au](mailto:enquiries@astecpaints.com.au)

Telephone: +61 8 8297 2000  
Facsimile: +61 8 8297 2555

Your Nearest Astec Paints Distributor is;

Revised Edition April, 2015

Astec Paints Resellers;

### **Australia Wide**

For a complete list of resellers,  
please visit the Contact Page  
of our website:

**[www.astecpaints.com.au/contact](http://www.astecpaints.com.au/contact)**

### **Overseas**

Please contact Head Office.